

Leidingwerk spanringen

Spanringen



Ø (mm)	Spanringen 2-delig smal zonder pakking		Pakkingringen EPDM		Spanringen breed zonder pakking		Snelspanringen 1mm met EPDM inlage*		Snelspanringen** 1 mm smal verzinkt	
	Art.nr.	Prijs	Art. nr.	Prijs	Art. nr.	Prijs	Art. nr.	Prijs	Art. nr.	Prijs
80	1670011		820170080		-		1670013		781114600	
100	1671011		820170100		-		1671013		781114601	
120	1672011		820170120		-		1672013		781114602	
125	1673011		820170125		-		1673013		781114603	
140	1674011		820170140		-		1674013		781114604	
150	1675011		820170150		1675001		1675013		781114605	
160	1676011		820170160		1676001		1676013		781114606	
180	1677011		820170180		1677001		1677013		781114607	
200	1678011		820170200		1678001		1678013		781114608	
225	1679011		820170225		1679001		1679013		781114610	
250	1680011		820170250		1680001		1680013		781114611	
275	1680511		820170275		1680501		1680513		-	
300	1681011		820170300		1681001		1681013		781114613	
315	1682011		-	-	1682001		1682013		781114614	
350	1683011		-	-	1683001		1683013		781114615	
400	1684011		-	-	1684001		1684013		781114617	
450	1685011		-	-	1685001		1685012		781114618	
500	1686011		-	-	1686001		1686012		781114619	
550	-	-	-	-	1687001		1687012		-	
600	-	-	-	-	1688001		1688012		-	
630	-	-	-	-	1689001		1689012		-	
650	-	-	-	-	1690001		1690012		-	
700	-	-	-	-	1691001		1691012		-	
750	-	-	-	-	1692001		1692012		-	
800	-	-	-	-	1693001		1693012		-	

Snelspanringen:
 Ø 80 t/m Ø 400 met scharnier en snelsluiting
 Vanaf 450 zonder scharnier en met een bout

Grotere diameters op aanvraag beschikbaar.

*) EPDM inlage is elektrisch geleidend (t/m d=400), >d=400 rode pvc inlage, niet geleidend.

**) Zonder pakking

Leidingwerk dakbeugels & flenzen

Dakbeugels en wandbevestiging

Flenzen



Ø (mm)	Dakbeugels		Wandbevestigingen		Ø (mm)	Onbehandeld		Verzinkt		Flenspakkingen oliebestendig	
	Art. nr.	Prijs	Art. nr.	Prijs		Art.nr.	Prijs	Art. nr.	Prijs	Art. nr.	Prijs
80	4670280		4660281		80	1610005		1670005		820150080	
100	4671280		4660281		100	1611005		1671005		820150100	
120	4672280		4660281		120	1612005		1672005		820150120	
125	4673280		4660281		125	1613005		1673005		820150125	
140	4674280		4660281		140	1614005		1674005		820150140	
150	4675280		4660281		150	1615005		1675005		820150150	
160	4676280		4660281		160	1616005		1676005		820150160	
180	4677280		4660282		180	1617005		1677005		820150180	
200	4678280		4660282		200	1618005		1678005		820150200	
225	4679280		4660282		225	1619005		1679005		820150225	
250	4680280		4660282		250	1620005		1680005		820150250	
275	4688289		4660282		275	1620505		1680505		820150275	
300	4681280		4660282		300	1621005		1681005		820150300	
315	4682280		4660282		315	1622005		1682005		820150315	
350	4683280		4660283		325	1623505		1683505		-	
400	4684280		4660284		350	1623005		1683005		820150350	
450	4685280		4660285		375	1624505		1684505		-	
500	4686280		4660286		400	1624005		1684005		820150400	
550	4687280		4660287		425	1625505		1685505		-	
600	4688280		4660288		450	1625005		1685005		820150450	
630	4689280		4660290		475	1626505		1686505		-	
650	4690280		4660292		500	1626005		1686005		820150500	
700	4691280		4660294		550	1627005		1687005		820150550	
750	4692280		4660296		600	1628005		1688005		820150600	
800	4693280		4660298		630	1629005		1689005		820150630	
850	4694280		-		650	1630005		1690005		820150650	
					700	1631005		1691005		820150700	
					750	1632005		1692005		820150750	
					800	1633005		1693005		820150800	
					850	1634005		1694005		820150850	
					900	1635005		1695005		820150900	
					950	1636005		1696005		820150950	
					1000	1637005		1697005		820151000	
					1250	1638005		1698005		820151250	

1 ophangpunt: Strip 28x2 mm verzinkt (met 1 verzonken bout, met moer M8).

*) Vanaf Ø 350 2 ophangpunten: Strip 40x3 mm verzinkt (exclusief draaieinden).

Grotere diameters op aanvraag beschikbaar.

Flensafmetingen: Ø 150 - 325: 25 x 5 mm
 Ø 80 - 140: 25 x 3 mm Ø 350 - 600: 30 x 6 mm

Grotere diameters op aanvraag beschikbaar.